

Detecting Cyber Anomalies in IoT Traffic Using a Dirichlet-Mixture Bayesian Model



Surani Matharaarachchi ¹ Saman Muthukumarana ²

¹New York Institue of Technology

²University of Manitoba

Abstract

This work compares two Bayesian models for detecting right-tail anomalies in **seasonal**, **over-dispersed** IoT count data. A single-regime Negative Binomial (NB) with a Fourier seasonal basis is contrasted with a Dirichlet-weighted NB mixture modeling *normal* and *spike* regimes. The mixture achieves higher AUC and better-calibrated spike probabilities on synthetic heavy-tailed data.

Problem

Goal: Flag transient, multiplicative spikes in hourly counts (e.g., packets, connections) under seasonality and over-dispersion.

Challenges: Seasonal, daily periodicity, rare heavy-tailed shocks that violate single-regime assumptions.

Data & Simulation


Time horizon T=200 hours with a **daily sinusoid** (period 24) and **no trend**. Underlying mean

$$\mu_t = \exp(2.5 + 0.25\sin(2\pi t/24)).$$

Counts follow NB2:

$$Y_t \sim NB(\mu_t, \alpha), \quad \alpha = 5.$$

We inject 6 random indices with multiplicative, heavy-tailed boosts for 1-2 hours \Rightarrow ground-truth anomalies.



Model A - Negative Binomial

Seasonality via a small Fourier basis $\mathbf{B}(t)$ (sin/cos of 24h harmonics):

 $\log \mu_t = a_0 + \mathbf{B}(t)^{\top} \gamma, \quad Y_t \sim \text{NB}(\mu_t, \alpha), \quad \alpha \sim \text{Gamma}(30, 0.3).$

Inference: ADVI in PyMC.

Score (right-tail): $S_t = 1 - \Pr(\tilde{Y}_t \ge y_t \mid \text{posterior})$.

Flag rule: p-right < 0.001.

Model B - Dirichlet Mixture NB

Mixture with shared dispersion and seasonal mean:

$$Y_t \sim \pi_0 \text{ NB}(\mu_t, \alpha) + \pi_1 \text{ NB}(k\mu_t, \alpha)$$

 $\pi \sim \text{Dirichlet}(98, 2), \log k \sim \mathcal{N}(\log 15, 0.4^2).$

Posterior responsibility for the spike component:

$$r_t = \Pr(\text{spike} \mid y_t, \theta) = \frac{\pi_1 p(y_t \mid k\mu_t, \alpha)}{\pi_0 p(y_t \mid \mu_t, \alpha) + \pi_1 p(y_t \mid k\mu_t, \alpha)}.$$

Score: $S_t = \mathbb{E}[r_t]$. Flag rule: $S_t > 0.9$.

Results




Figure 1. NB model — Posterior Predictive (AUC = 0.875)




Figure 2. Dirichlet Mixture — Posterior Predictive (AUC = 0.912)

The two posterior predictive plots compare the single NB model and the Dirichlet-Mixture model, highlighting the improved ability of the mixture to capture rare and extreme spikes in IoT traffic.

Limitations & Next Steps

- Extend from single-device to multi-host detection with shared priors for coordinated alerts.
- Capture multi-hour intrusion patterns using temporal or HMM-based modeling.
- Incorporate network context and enable online Bayesian updates for real-time monitoring.

Summary

This work introduces a Dirichlet-Mixture Negative Binomial model for detecting rare spikes in seasonal IoT traffic. The proposed model explicitly separates *normal* and *spike* regimes through Dirichlet mixing, improving AUC, and interpretability compared to a standard NB approach.

References

- [1] Andrew Gelman, John B Carlin, Hal S Stern, David B Dunson, Aki Vehtari, and Donald B Rubin. *Bayesian Data Analysis*. Chapman and Hall/CRC, 3 edition, 2013.
- [2] Radford M Neal. Markov chain sampling methods for Dirichlet process mixture models. Journal of Computational and Graphical Statistics, 9(2):249–265, 2000.
- [3] José A. Perusquía, Jim E. Griffin, and Cristiano Villa. Bayesian models applied to cyber security anomaly detection problems. *arXiv preprint arXiv:2003.10360*, 2020. doi: 10. 48550/arXiv.2003.10360. URL https://arxiv.org/abs/2003.10360.
- [4] PyMC Contributors. Pymc: Probabilistic programming in python. https://www.pymc.io, 2024. Accessed: 2025-09-15.